
# 800 WOG THREADED "Y" TYPE CHECK VALVE








**DESIGN FEATURES:**

Investment Cast Body & Cap
Screwed-In Cap
Connecting Threads: ANSI B2. 1/BS21

Standards:
ASTM-A351-CF8M/ EN10213 1.4408,
DIN 259/DIN2999, ANSI B2.1 / BS21, ISO 228

**BASINÇ / SICAKLIK ORANI**
PRESSURE TEMPERATURE RATINGS
**(BODY)**




| Malzeme Listesi / Material Lists | | | |
|---|---|---|---|
| No | Parça Adı / Part Name | Malzeme / Material | Adet / Q'ty |
| 1 | GÖVDE / BODY | ASTM A351 Gr.CF8M | 1 |
| 2 | GİRİŞ-ÇIKIŞ / CAP | ASTM A351 Gr.CF8M | 1 |
| 3 | YAY / SPRING | ASTM A351 Gr.CF8M | 1 |
| 4 | DİSK / DISC | SS304 | 1 |
| 5 | DİSK CONTASI / SEAT | TEFLON | 4.-12 |
| 6 | PUL / WASHER | TEFLON | 4.-12 |
| 7 | CİVATA / BOLT | SS304 | 1 |
| 8 | SIZDIRMAZLIK CONTASI / GASKET | TEFLON | 1 |

| Ölçüler / Dimensions | | | | | |
|---|---|---|---|---|---|
| Size | | A | B | C | Cv |
| inch | mm | mm | mm | mm | Factor |
| 1/4" | 8 | 65 | 46.0 | 19 | 6.0 |
| 3/8" | 10 | 65 | 46.0 | 19 | 12.0 |
| 1/2" | 15 | 65 | 46.0 | 19 | 19 |
| 3/4" | 20 | 80 | 58.0 | 23 | 37.0 |
| 1" | 25 | 90 | 69.0 | 27 | 64.0 |
| 11/4" | 32 | 105 | 75.0 | 32 | 103.0 |
| 11/2" | 40 | 120 | 85.0 | 41 | 143.0 |
| 2" | 50 | 140 | 98.0 | 50 | 360.0 |